


PTW Safety Checklist No. 57



GENERAL RIGGING AND LIFTING WORK (OTHER THAN CRANES)

Other Checklists that may be relevant:		24 , 27 , 51 , 55
Permit Number:		Date:
Rev 2.0	Issue Date: 13/12/2017	Authorised By: PSM

PRIOR TO PERMIT ISSUE:

- | | | Y | N | N/A |
|---|--|--------------------------|---|--------------------------|
| 1 | If the lift is >500kgs and lifted greater than 5m?

If answer is Yes, appropriate fall protection is required. All persons wearing fall protection shall hold, or be supervised by a person holding NZQA unit standard 15757, 23229 or 25045.

Name: _____ NZQA Unit held: _____
Name: _____ NZQA Unit held: _____
Name: _____ NZQA Unit held: _____ | <input type="checkbox"/> | | <input type="checkbox"/> |
| 2 | If pipework is to be used as the point of lift, approval must be gained from a mechanical engineer. Approval attached. | <input type="checkbox"/> | | <input type="checkbox"/> |
| 3 | If lifting over or near live process plant, agree controls with PI. | <input type="checkbox"/> | | <input type="checkbox"/> |

PRIOR TO COMMENCING WORK:

- | | | | | |
|----|---|--------------------------|--------------------------|--------------------------|
| 4 | All rigging equipment is in sound condition and within certification and marked with SWL. | <input type="checkbox"/> | | |
| 5 | Sling protectors shall be used around sharp edges. | <input type="checkbox"/> | | <input type="checkbox"/> |
| 6 | Tape, barriers and / or signs have been erected. | <input type="checkbox"/> | | <input type="checkbox"/> |
| 7 | Centre of gravity of the load has been determined? | <input type="checkbox"/> | | |
| 8 | Are tag lines in place where required? | <input type="checkbox"/> | | <input type="checkbox"/> |
| 9 | Prior to the use of lifting lugs on manway flange closures, hatches or motors visual checks have been carried out by a Facilities Inspector or Mechanical Engineer. | <input type="checkbox"/> | <input type="checkbox"/> | |
| 10 | Lifting plan discussed between all parties immediately prior to lift including recovery measures. | <input type="checkbox"/> | <input type="checkbox"/> | |
| 11 | The PICOL and the Rigger must hold the required competencies as listed below: | | | |

Position/Role	Required Competencies And Qualifications (Unit Standards)	Competency held by (insert name)
Person-in-charge of lift (PICOL)	Must hold at least one of the following NZQA Unit Standards: <ul style="list-style-type: none"> • 26350 – Use common rigging equipment to lift and move loads • 9559 – Sling routine loads and communicate during crane operations in a petrochemical workplace • 3789 – Sling regular loads and communicate during crane operations 	
Dogman / Banksman / Rigger / Slinger	Must hold at least one the following NZQA Unit Standards or Todd Energy approved equivalents: <ul style="list-style-type: none"> • 26350 – Use common rigging equipment to lift and move loads • 9559 – Sling routine loads and communicate during crane operations in a petrochemical workplace • 3789 - Sling regular loads and communicate during crane operations 	